

STS650



Mounting Pattern
200 x 100 to
600 x 600mm



Max Load
200lb
(90.7kg)




- 3.82"-12.00" (97-305mm) display extension allows for post-installation servicing and component storage behind display
- Universal mount fits displays with mounting patterns 200 x 100 to 600 x 400mm (600 x 600mm with included bolt-on extenders)
- Adjustable up to 15° of forward tilt and -2° of backward tilt for the optimal viewing angle
- Optional IncreLok™ feature offers fixed tilt angles of -2°, 0°, 5°, 10°, and 15°
- Menu board style wall plate with open frame design (compatible with IB14X9-W In-Wall Box)
- Extendable Adaptors can be tensioned to any depth to ensure display sits flush in recessed applications
- Up to 1/2" (12mm) of post-installation leveling
- Center keyhole for easy leveling and installation
- Optional Accessory: Universal AV Component Mount (ACC-UCM2) allows components to be installed, configured and cabled off-site, and quickly attaches to the mount which reduces on-site installation time

SMARTMOUNT®

Universal Scissor Wall Mount

FOR 39" TO 85"+ DISPLAYS*

Peerless-AV's SmartMount® Universal Scissor Wall Mount is the optimal mounting solution for UC/VC applications and recessed walls as the STS650 allows for convenient access to components stored behind the display. The STS650's extendable adaptors allow the display to be pulled 12" (305 mm) from the wall to easily access the back of the display, and can be locked into place when the installation or maintenance is completed. Installation of the display is a breeze with the Hook-and-Hang™ feature, and the mount's open access design provides the maximum open area on the wall to allow flexible placement for outlets and/or in-wall boxes. Post-installation leveling and side-to-side adjustability features allow for fine tuning of the mounted display for the perfect position in any corporate conference room, digital signage application or hospitality setting.



Fully adjustable +15/-2° tilt with IncreLok™



Shown with (2) optional ACC-UCM2 Universal AV Component Mounts



Please visit peerless-av.com/en-us/patents for patent information.

*This display size range is simply a guideline for product selection. Displays larger than the screen size range may still be compatible as long as they fall within the VESA® pattern and max weight of the Peerless-AV® product.

STS650 SmartMount® Universal Scissor Wall Mount for 39" to 85"+ Displays

Product Specifications

	DIMENSIONS (W x H x D)	PRODUCT WEIGHT	LOAD CAPACITY	FINISH	AVAILABLE COLORS
STS650	28.84" x 26.90" x 3.82"-12.00" (732 x 683 x 97-305mm)	35.5lb (16.1kg)	200lb (90.7kg)	Scratch Resistant Fused Epoxy	Semi-Gloss Black


Package Specifications

	PACKAGE SIZE (W x H x D)	PACKAGE SHIP WEIGHT	PACKAGE UPC CODE	PACKAGE CONTENTS	UNITS IN PACKAGE
STS650	32.70" x 18.20" x 4.50" (830 x 463 x 115mm)	40.0lb (18.1kg)	735029354376	Wall Mount, Wall and Display Installation Hardware, Installation Instructions	1

Accessories

- ACC-UCM2:** Universal AV Component Mount for STS650
- ACC-SB2:** Universal UC/VC Soundbar Mount
- ACC415:** 4-Pack Metal Stud Fastener Kit
- ACC925:** Security Fasteners for V200x200 to V800x400 Mounts
- ACC-M835:** Security Fast-Pack, M8x25 & M8x35
- ACC-V900X:** 600, 800 or 900mm Extension for 400mm Adaptors

- ACC-V1500X:** Accessory Adaptor Rails for VESA® 1000, 1200 or 1500mm Wide Mounting Patterns
- ACSBR1:** Universal Sound Bar Mounting Kit
- ACSBR2:** Universal Sound Bar Mount
- IBA4-W:** Easy Mount Recessed Low Voltage Cable Plate
- IB14X9-W:** 14"x9" In-Wall Box
- IB14X9-AC-W:** 14"x9" In-Wall Box with Duplex Surge Protector



Architect Specifications

The SmartMount® Universal Scissor Wall Mount shall be a Peerless-AV model STS650 and shall be located where indicated on the plans. Assembly and installation shall be done according to instructions provided by the manufacturer.

Visit peerless-av.com to see the complete line of AV solutions from Peerless-AV, including outdoor displays, kiosks, display mounts, projector mounts, carts/stands, and a full assortment of accessories.

Peerless-AV
 2300 White Oak Circle
 Aurora, IL 60502
 USA
(800) 865-2112
(630) 375-5100

Peerless-AV EMEA
 Unit 2 Curo Park
 Frogmore, St. Albans
 Hertfordshire, AL2 2DD
 United Kingdom
+44 (0) 1923 200 100

Peerless-AV B.V.
 Papendorpseweg 75
 3528 BJ Utrecht
 The Netherlands
+31 (0) 70 770 8037

Peerless-AV Latin America
 Av. de las Industrias 413
 Parque Industrial Escobedo
 General Escobedo, N.L.,
 México, 66062
+52 (81) 8384-8300

